


DT7B-BS-C

Specifications

Model NO.	DT7B-BS-C	
Upgrade From	YT7B-BS	
Nominal Voltage	12V	
Rated Capacity (10 hours rate)	6.5Ah	
Dimensions	Length	150 mm (5.91 inches)
	Width	65 mm (2.56 inches)
	Height	93 mm (3.66 inches)
	Total Height	93 mm (3.66 inches)
Approx. Weight W/O . ACID	1.70 kg (3.75 Lbs)	
Approx. ACID Per Battery	0.31 L	
Charge Current (A)	0.65 A (14.4V constant voltage charge)	



Dimensions



Characteristics

Capacity 25°C (77°F)	10hours rate (0.65A to 10.5V)	6.5 Ah
	5hours rate (1.3 A to 10.2V)	5.5 Ah
	1C (6.5 A to 9.6V)	2.9 Ah
	3C (19.5 A to 9.6V)	2.3 Ah
Cold Cranking Amperes(-18°C SAE Standard)	85 A	
Cold Cranking Amperes(-18°C EN Standard)	85 A	
Internal Resistance (at 1KHz)	Approx .8mΩ	
Operating Temperature Range	Charge	0°C (32°F) to 40°C (104°F)
	Discharge	-30°C (-22°F) to 50°C (122°F)
	Storage	-15°C (5°F) to 40°C (104°F)
Life Expectancy (Cycle Use)	60% depth of discharge 250 cycles	
	30% depth of discharge 400 cycles	
Charge Retention (self-discharge life) at 20°C (68°F)	1 month	85%
	3 month	80%
	6 month	75%
Warranty	1 year	
Case Material	PP	

(V)
FOR 12V
BATTERY

Discharge Time VS. Discharge Current(25°C)

