

MG10ZS-C

Specifications


Model NO.	MG10ZS-C	
Upgrade From	YTZ10S	
Nominal Voltage	12V	
Rated Capacity (10 hours rate)	8.6Ah	
Dimensions	Length	150 mm (5.91 inches)
	Width	86 mm (3.39 inches)
	Height	94 mm (3.70 inches)
	Total Height	94 mm (3.70 inches)
Approx. Weight	2.77 kg (6.11 Lbs)	
Charge Current (A)	0.86A (14.4V constant voltage charge)	



Characteristics

Capacity 25°C (77°F)	10 hours rate (0.86A to 10.5V)	8.6 Ah
	5 hours rate (1.7 A to 10.2V)	7.3 Ah
	1C (8.6 A to 9.6V)	3.9 Ah
	3C (25.8 A to 9.6V)	3.1 Ah
Cranking Amperes (by Midtronic Tester)		255 A
Cold Cranking Amperes (-18°C SAE Standard)		145 A
Cold Cranking Amperes (-18°C EN Standard)		145 A
Internal Resistance (at 1KHz)		Approx. 12mΩ
Operating Temperature Range	Charge	0°C (32°F) to 40°C (104°F)
	Discharge	-30°C (-22°F) to 50°C (122°F)
	Storage	-15°C (5°F) to 40°C (104°F)
Life Expectancy (Cycle Use)	60% depth of discharge 250 cycles	
	30% depth of discharge 400 cycles	
Charge Retention (self-discharge life) at 20°C (68°F)	1 month	92%
	3 month	90%
	6 month	80%
Warranty	2 years	
Case Material	ABS	

Dimensions



(V)
FOR 12V
BATTERY

Discharge Time VS. Discharge Current (25°C)

