



|                               |  |  |
|-------------------------------|--|--|
| Type no.                      | EFB 740 17                             |  |
| Article no.                   | 012740170101                           |  |
| Standards                     | DIN EN 50342-1, 50342-4                |  |
| Application                   | Starter battery                        |  |
| <b>Electrical data</b>        |  |  |
| Rated voltage                 | 12V                                    |  |
| Rated capacity                | 240 Ah (K20)                           |  |
| Cold start current            | 1200 A (EN)                            |  |
| <b>Dimensions and weights</b> |  |  |
| Box                           | C                                      |  |
| Length max.                   | 517mm                                  |  |
| Width max.                    | 273mm                                  |  |
| Box height max.               | 212mm                                  |  |
| Total height max.             | 240mm                                  |  |
| Battery weight                | Ca. 60,0 kg (+/- 5 %)                  |  |
| Electrolyte density           | Approx. 1,28 kg/l                      |  |
| Electrolyte                   | Diluted sulphuric acid                 |  |
| Items/pallet                  | 18                                     |  |
| Pallet ID                     | Euro pallet                            |  |
| Items per layer               | 6                                      |  |
| <b>Features</b>               |  |  |
| Base hold-down                | B00                                    |  |
| Layout                        | 3                                      |  |
| Terminal                      | 1                                      |  |
| Separator                     | PE bag separator with glass mat        |  |
| Degassing                     | Battery with central degassing         |  |
| Flame arrester                | Integrated                             |  |
| Performance identification    | W4 - C2 - >V3 - E3                     |  |
| <b>Maintenance 1)</b>         |  |  |
| Water consumption             | W4                                     |  |
| Refill water                  | Distilled or demineralised (DIN 43530) |  |
| Self-discharge                | Approx. 3 % per month                  |  |
| Charging current              | Approx. 1/10 of the rated capacity     |  |
| Charging voltage 2)           | max. 14,8 V                            |  |



1) All the listed values relate to room temperature +25° C

2) Recommendation with an external, voltage-regulated charge. Attention: Temperature compensation in case of deviation!

1 Document DBTBAT00339 prepared on 2020-09-30 ; Rights relating to changes and errors retained.  
original