

DT400 BATTERY TESTER



DIGITAL
ANALYZER
888

12V

Pb-Ca

Wet












Gel

MF

DESCRIPTION

Intelligent digital tester used to verify the charge status and start current capacity of 12V batteries (WET,GEL,AGM,PbCa). It is very compact, practical, easy to use and allows operations without disconnecting the battery from the vehicle; this is an enormous time saver during testing operations which become quick and easy to perform. The practical digital display and LED system provide instant viewing of the required information with high quality precision and efficient battery control. Moreover, the possibility to select the reference standard used by the battery manufacturers (EN,IEC,DIN,SAE,CA-MCA), each of which refers to the different ranges of start currents, is further confirmation of the exceptional versatility of this instrument.

TECHNICAL DATA

 CODE	CODE 802605	 Battery voltage	12 V	 A_h	Battery range 20-200 Ah
 A_{MIN} MAX	Starting current range EN 185/1125-EN A	 A_{MIN} MAX	Starting current range IEC 130/790-IEC A	 A_{MIN} MAX	Starting current range DIN 110/670-DIN A
 A_{MIN} MAX	Starting current range SAE 200/1200-SAE A	 A_{MIN} MAX	Starting cur.range CA(MCA) 240/1440-CA(MCA) A	 T^{°C}	Operating temper.(min-max) 0 - 40 °C
 LxWxH	DIMENSIONS 7,8 x 2,2 x 14,5 cm	 kg	WEIGHT 0,18 kg		

DOWNLOAD



CATALOG IMAGE



INSTRUCTION MANUAL