

STS700 BATTERY TESTER



DESCRIPTION

Digital tester to check the status of the battery, the starting efficiency (CCA), the starter system and the alternator circuit of the vehicle.

Selectable international standards both for cars and motorbikes, which correspond to different starting current ranges used by the battery manufacturer.

Handy and small in size, it can operate on 12V batteries (WET, GEL, MF, AGM, PbCa, EFB) both disconnected and connected to the vehicle, making testing operations quick and easy.

The colour graphic display makes the product intuitive and easy to use.










It is possible to graphically display the performance of the battery voltage over time.

Saving and printing of reports via PC connection.

Features:

- for WET, GEL, MF, AGM, PbCa, EFB batteries from 8-240 Ah at 12V;
- tests performed: battery status, starting capability (CCA), starter system, vehicle alternator circuit;
- selectable reference standards for cars and motorbikes;
- tests can be performed with the battery disconnected or connected to the vehicle;
- color graphic display;
- graphic display of voltage performance over time;
- multilingual: EN, IT, FR, DE, ES, RU, PT, NL, PL, JP, CN, KO;
- saving and printing of reports via PC connection.

TECHNICAL DATA

	CODE 804243		Battery voltage 12 V		Battery range 8-240 Ah
	Starting current range EN 185/1125-EN A		Starting current range IEC 100/1400-IEC-DIN A		Starting current range DIN 26A17/245H2-JIS A
	Starting current range SAE 200/2000-SAE A		Starting cur.range CA(MCA) 100/2000-CA(MCA)-CCA-BCI A		Starting current range JIS 12N5.5-4A,12N5.5A-3B (MOT) A



Operating temper.(min-max)
0 - 40 °C



DIMENSIONS
8,0 x 2,3 x 15,0 cm



WEIGHT
0,27 kg

DOWNLOAD



CATALOG IMAGE



INSTRUCTION MANUAL



SOFTWARE/APP