

DTP900 BATTERY TESTER



DESCRIPTION

Digital tester to check the status of the battery, the starting efficiency (CCA), the starter system and the alternator circuit of the vehicle.

Selectable reference international standards for vehicles to which the various starting amp ranges used by the battery manufacturer correspond.

Practical and compact, it allows operation on 12V/24V batteries (WET, GEL, MF, AGM, PbCa, EFB) both disconnected and connected to the vehicle, facilitating testing operations which are rapid and easy to carry out.













It automatically compensates temperature for more precise detection.

The backlit LCD screen facilitates data reading, even in poorly lit environments. Equipped with a built-in printer to print reports.

Features:

- for WET, GEL, MF, AGM, PbCa, EFB batteries from 4-250 Ah at 12V/24V;
- tests carried out: battery status, starting efficiency (CCA), starting system, alternator circuit of the vehicle;
- selectable reference standard for the vehicle;
- tests can be carried out with battery disconnected or connected to the vehicle;
- backlit LCD display;
- multilingual: EN, IT, FR, DE, ES, PT;
- direct printing of reports using built-in printer.

TECHNICAL DATA

 CODE	CODE 804244	 Battery voltage	12-24 V	 Battery range	4-250 Ah
 Starting current range EN	40/1885-EN A	 Starting current range IEC	30/1320-IEC A	 Starting current range DIN	25/1120-DIN A
 Starting current range SAE	40/2000-SAE-CCA A	 Starting cur.range CA(MCA)	50/2400-CA(MCA) A	 Starting current range JIS	26A17/245H2-JIS A
 Operating temper.(min-max)	0 - 40 °C	 DIMENSIONS	9,8 x 7,8 x 27,5 cm	 WEIGHT	0,714 kg

DOWNLOAD



CATALOG IMAGE



INSTRUCTION MANUAL