

AUTOTRONIC 25



Tronic



- Battery charger with TRONIC technology for WET, GEL, AGM, MF, PbCa, EFB 12/24V batteries.
- BOOST (fast charge) function.
- Loading current display, protection against pole inversion, short circuit.

DESCRIPTION

Battery charger with electronic control of the charging current, automatic interruption and restart (TRONIC), for charging lead-acid batteries with 12V/24V voltage.

Fit with switches to choose either anormal charge (MIN) or quick charge (BOOST) in the buffer mode (TRONIC) or drooping characteristic mode (CHARGE).







The buffer automatic charge is adequate for maintenance free sealed batteries (GEL/AGM/START-STOP), while the drooping characteristic charge is adequate for free-electrolyte batteries (WET).

Features:

- choice of output voltage, type of charge, charging mode
- display of charging current
- protection against overloads and polarity reversal.



TECHNICAL DATA

CODE	CODE 807540	V_{1PH}	SINGLEPHASE MAINS VOLTAGE 230 V	F	MAINS FREQUENCY 50 / 60 Hz
P	CHARGING ABSORBED POWER 300 W		CHARGING VOLTAGE 12 / 24 V	A_{EFF}	EFFECTIVE CHARGING CURRENT 18 / 12 A
A_{EN}	RATED CHAR.CUR.EN60335-2-29 12 / 8 A		MIN.RATED REFERENCE CAPAC. 30 / 20 Ah		MAX.RATED REFERENCE CAPAC. 225 / 180 Ah
	ADJUSTMENT POSITIONS 4		DIMENSIONS (LxWxH) 22,5 x 29 x 20,5 cm		WEIGHT 7,2 kg

SUPPLIED ACCESSORIES



COLORADO 40R POSITIVE CLAMP 40A
712623



COLORADO 40B WORK CLAMP 40A
712624

ON REQUEST ACCESSORIES



FUSES 20A 10 PCS
802257

DOWNLOAD



CATALOG IMAGE



INSTRUCTION MANUAL



SPARE PARTS LIST