

# ALASKA 150 START



**ELEMENTS** *Tronic*

12V

Pb-Ca

Wet

Gel

AGM

EFB

MF

- Battery charger and trickle charger with TRONIC technology for 12V lead batteries for motorbikes, cars, vans, etc.
- Normal CHARGE, BOOST charge, automatic charge and trickle charge in TRONIC mode of WET, GEL, AGM, MF, PbCa, EFB.
- CHARGE, TRONIC mode selection. Display of charging current (CHARGE). LED signalling of the charge, charging ended and trickle charge (TRONIC).
- Protection against overcharging and pole inversion.

## DESCRIPTION

Battery charger and maintainer with electronic control of the charging current, automatic interruption and restart (TRONIC), for charging lead-acid batteries with 12V voltage of motorcycles, vehicles, vans, light trucks.







Charge options: normal CHARGE, BOOST quick charge, automatic TRONIC charge and maintenance of WET, GEL, AGM, MF, PbCa, EFB batteries.

Features:

- Choice of CHARGE, TRONIC mode;
- Visualization of charging current (CHARGE);
- Warning LED to indicate battery charge status, end of charge, maintenance (TRONIC);
- Choice of output voltage, charge voltage, start;
- Protection against overloads and polarity reversal.



## TECHNICAL DATA

<b>CODE</b>	CODE 807576	<b>V<sub>1PH</sub></b>	SINGLEPHASE MAINS VOLTAGE 230 V	<b>F</b>	MAINS FREQUENCY 50 / 60 Hz
<b>P</b>	CHARGING ABSORBED POWER 220 W		CHARGING VOLTAGE 12 V	<b>A<sub>EFF</sub></b>	EFFECTIVE CHARGING CURRENT 20 A
<b>A<sub>EN</sub></b>	RATED CHAR.CUR.EN60335-2-29 12 A	<b>A<sub>1V/C</sub></b>	QUICK CHARGE/START CURRENT 50 / 100 A		MIN.RATED REFERENCE CAPAC. 10 Ah
	MAX.RATED REFERENCE CAPAC. 200 Ah		ADJUSTMENT POSITIONS 2		DIMENSIONS (LxWxH) 24,5 x 19,5 x 13 cm
	WEIGHT 5,9 kg				

DOWNLOAD



CATALOG IMAGE



INSTRUCTION MANUAL

USEFUL LINKS



VIDEO