

# ALASKA 200 START



**ELEMENTS** *Tronic*



- Battery charger and trickle charger with TRONIC technology for 12/24V lead batteries for motorbikes, cars, vans, etc.
- Normal CHARGE, BOOST charge, automatic charge and trickle charge in TRONIC mode of WET, GEL, AGM batteries: SPIRAL, MF, START-STOP.
- CHARGE, TRONIC mode selection. Display of charging current (CHARGE). LED signalling of the charge, charging ended and trickle charge (TRONIC).
- Protection against overcharging and pole inversion.

## DESCRIPTION

Battery charger and maintainer with electronic control of the charging current, automatic interruption and restart (TRONIC), for charging lead-acid batteries with 12/24V voltage of motorcycles, vehicles, vans, light trucks.







Charge options: normal CHARGE, BOOST quick charge, automatic TRONIC charge and maintenance of WET,GEL,AGM: SPIRAL,MF, START-STOP batteries.

Features:

- choice of CHARGE, TRONIC mode
- visualization of charging current (CHARGE)
- warning LED to indicate battery charge status, end of charge, maintenance (TRONIC)
- choice of output voltage, charge voltage, start
- protection against overloads and polarity reversal.



## TECHNICAL DATA

<b>CODE</b>	CODE 807577	<b>V<sub>1PH</sub></b>	SINGLEPHASE MAINS VOLTAGE 230 V	<b>F</b>	MAINS FREQUENCY 50 / 60 Hz
<b>P<sub>CHARGE</sub></b>	CHARGING ABSORBED POWER 0,3 kW	<b>P<sub>START</sub></b>	STARTING ABSORBED POWER 2,2 kW		CHARGE AND STARTING VOLTAG. 12 / 24 V
<b>A<sub>EFF</sub></b>	EFFECTIVE CHARGING CURRENT 25 / 12 A	<b>A<sub>EN</sub></b>	RATED CHAR.CUR.EN60335-2-29 15 / 8 A	<b>A<sub>1V/C</sub></b>	START CUR.1V/C EN60335-2-29 100 A
<b>A<sub>START MAX</sub></b>	MAX STARTING CURRENT 150 A		MIN.RATED REFERENCE CAPAC. 25 / 30 Ah		MAX.RATED REFERENCE CAPAC. 300 / 160 Ah
	ADJUSTMENT POSITIONS 2		DIMENSIONS (LxWxH) 24,5 x 19,5 x13 cm		WEIGHT 7,57 kg

DOWNLOAD



CATALOG IMAGE



INSTRUCTION MANUAL

USEFUL LINKS



VIDEO