

## T-CHARGE 20



*Pulse* TRONIC  
**Tronic**



COLD



CHARGE



SUPPLY



RECOVERY

- Multi-functional electronic battery charger, trickle charger and tester for WET, GEL, AGM, MF, PbCa, EFB, Li 12/24V batteries.
- Automatic charging and trickle charging in Pulse Tronic. Choice 2 charge voltages: 12V/24V. Charging level led display.
- Advanced functions: AGM for charging and trickle charging of AGM batteries; COLD for charging and trickle charging of batteries at low temperatures; RECOVERY to recover sulphated batteries.
- IP65 level ensures protection against dust, water and humidity. Compact and lightweight, for easy transport and positioning.
- Safety guaranteed by protection against overcharging, short circuit and pole inversion.
- Cable with clamps and cable with eyelets.

## DESCRIPTION

Multi-functional electronic battery charger and trickle charger for WET, GEL, AGM, MF, PbCa, EFB, 12V/24V batteries.

Choice of 2 charging voltages in Pulse Tronic mode: 12V / 24V. Automatic choice of charging current.

Advanced functions for charging and maintenance of batteries at low temperatures and for AGM batteries. Activation of the RECOVERY function enables resetting of sulphated batteries.






Features:

- Automatic charge and maintenance in Pulse Tronic;
- 2 charging voltages;
- Led display of battery charge level;
- AGM function to charge and maintain AGM batteries;
- COLD function to charge and maintain batteries at low temperatures;
- RECOVERY function to recover sulphated batteries;
- SUPPLY function for stable power supply during battery changing;
- Protection against overcharge, short circuit and polarity reversal.


Complete with cable with clamps and cable with eyelets.



## TECHNICAL DATA

<b>CODE</b>	CODE 807594	<b>V<sub>1PH</sub></b>	SINGLEPHASE MAINS VOLTAGE 230 V	<b>F</b>	MAINS FREQUENCY 50 / 60 Hz
<b>P</b>	CHARGING ABSORBED POWER 115 W		CHARGING VOLTAGE 12 / 24 V	<b>A<sub>EFF</sub></b>	EFFECTIVE CHARGING CURRENT 8 / 4 A
<b>A<sub>EN</sub></b>	RATED CHAR.CUR.EN60335-2-29 8 / 4 A		MIN.RATED REFERENCE CAPAC. 5 Ah		MAX.RATED REFERENCE CAPAC. 180 Ah
<b>IP</b>	PROTECTION DEGREE IP65		DIMENSIONS (LxWxH) 27 x 12 x 6,7 cm		WEIGHT 1,33 kg

ON REQUEST ACCESSORIES



MAGNETS 2 PCS  
803088

DOWNLOAD



CATALOG IMAGE



INSTRUCTION MANUAL



BROCHURE