LEDriving SL W5W WHITE

Ideal replacement for any vehicle



Suitable for various vehicle exterior applications Available in Cool White

Replaces conventional W5W lamps

Easy upgrade to LED technology with plug & play solutions



Reliable OSRAM quality stands for less lamp replacements 4-year OSRAM guarantee (refer to www.osram.com/am-guarantee for precise conditions)



Suitable LED replacement for W5W

LEDriving SL W5W replacement lamps offer a modern and intense light with a color temperature up to 6,000 Kelvin. These replacement lamps are suitable for all conventional W5W lamp bases. In comparison to standard lamps, these LED retrofit lamps use up to 80% less energy. OSRAM offers a 4 year guarantee for these LEDriving SL lamps.These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Technical data

Product information

Order reference 2825DWP			
Product type (off-road vs. on-road)	Off-road ≙ W5W		
Application (Category and Product specific)	Mainly used for signal/ indicator/ interior applications		


Electrical data

Power input	1.12 W
Nominal voltage	12.0 V
Nominal wattage	0.80 W
Test voltage	13.5 V
Power input tolerance	±10 %

Photometrical data

Luminous flux	70 lm
Luminous flux tolerance	±25 %
Color temperature	6000 К
Light color LED	Cool white

Dimensions & weight



Diameter	10.0 mm
Product weight	1.70 g
Length	26.8 mm

Lifespan

Lifespan B3	1500 h
Lifespan Tc	4000 h
Guarantee	4 years

Additional product data

Pase (standard designation)	W2.1x9.5d	
Base (standard designation)	W2.1X9.50	
Capabilities		
Technology	LED ¹⁾	
¹⁾ Light-emitting diode lamp		
Country specific categorizations		
Order reference	2825DWP	

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)		
Date of Declaration	07-03-2024	
Primary Article Identifier	4052899620810 4062172348638 4062172352055 4062172401258	
Candidate List Substance 1	Lead	
CAS No. of substance 1	7439-92-1	
Safe Use Instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.	
Declaration No. in SCIP database	d493a7ba-1e50-4adf-97d4-fe52b1e7a9c4	

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899620810	LEDriving SL ≙ W5W	Blister 2	- x - x -		20.00 g
4052899620827	LEDriving SL ≙ W5W	Shipping carton box 20	140 mm x 105 mm x 146 mm	2.15 dm³	198.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Download Data

	File
*	Brochures LEDriving Retrofits - Exchange overview (EN)

Safety advice

Canbus compatible

Coloured lamps for usage behind coloured glass

Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

